Sieve Magnet



At A Glance



Our sieve magnet is a unique lightweight, full stainless steel design which reduces the stress on the sieve that other types often cause.

The unit is positioned beneath the sieve screen allowing excellent separation to be achieved. Due to the high intensity of the magnetic field within the unit, even sub-micron sized particles generated by the wear of the sieve screen can be successfully attracted.

Benefits

- Easy to install
- Reduces 'spark' risk
- Meets audit requirements
- Removes micron sized contaminants
- Protects against screen wear and failure
- Static dissipative all metal construction

Performance

Magnetic Performance	7000, 9000, 11000 and 12000 Gauss		
Performance Reading	On tube surface		
Magnet Grade	N35 & N45 – Inspected and confirmed via hysterograph		
	prior to use		
Temperature	-4°C / +194°F		

Suitability

Suitable Products	
Suitable Location	

Dry powders, granulates and liquids etc. Post sieve screen



Materials

Magnetic Material
Tubing
Other Parts
Surface Finish

Rare Earth Neodymium Iron Boron - (NdFeb) 316 grade stainless steel 316 grade stainless steel Polished to 0.6µm

Cleaning

Simply remove the top pan and screen from the sieve. The magnet can now be removed from the bottom pan and placed onto a non-magnetic surface. Using the supplied cleaning tool, simply scrape all attracted contamination to each rod end where it can be removed.

Options


- Pharmaceutical specification ATEX certified
- Magnet and screen metal detectable silicon rubber seal
- Higher temperature versions available





Sieve Magnet





Part Number	A (inches)	B (inches)	Number Of Rods	Weight (lbs)	Gauss	To Be Used In Types
SU600/M/SS	21.5	1.25	7	31	7,000	RussellFinex - Compact
SU600/M/HS	21.5	1.25	7	31	9,000	RussellFinex - Compact
SU600/M/SHS	21.5	1.25	7	31	11,000	RussellFinex - Compact

For non-standard sizes, please contact sales@eclipsetoolsinc.com

Metal Detectable Seal

The Eclipse Magnetics metal detectable sieve magnet and screen seal is a patented rubber seal that allows for easy detection in case of breakage due to excessive sieve wear.

The magnet and screen seal differ in size and can be fitted to the patented sieve magnet. These seals can also be retro fitted to existing sieve magnets and screens from leading manufacturers. All materials used to manufacture these seals are listed in the FDA regulations.



If you have any more questions, require technical assistance or would like a quotation, please contact us.

www.eclipsetoolsinc.com

Eclipse Tools North America Inc. 442 Millen Road, Unit 9, Stoney Creek, Ontario, L8E 6H2, Canada T 1-800-260-2124 F 1-800-260-1410 sales@eclipsetoolsinc.com www.eclipsetoolsinc.com While every effort has been made to ensure the accuracy of the information in this publication please note that specifications may change without notice.





A world leader in magnetic technology